

EXCAVATORS

HITACHI

Reliable Solutions

LANDCROS



A REPUTATION BUILT ON RELIABILITY

Hitachi Construction Machinery Americas

ZX17U-5N



ZX17U-5N SPECIFICATIONS



Weight **3,790 lbs / 1,720 kg**

Overall Width **Retract: 3' 3" / 0.99 m
Extend: 4' 2" / 1.28 m**

Net Rated Power **14.7 HP / 10.8 kW**

Engine **Yanmar 3TNV74F**

Aux. Hyd. Flow **7.9 GPM / 30.0 LPM**

Arm Length* **3' 1" / 0.93 m**

Max Digging Reach
at Ground Level **12' 2" / 3.72 m**

Max Dig Depth **7' 2" / 2.19 m**

Arm Breakout **1,993 lbf / 8.6 kN**

Bucket Breakout **3,598 lbf / 16 kN**

*Rubber Shoe, 3' 1" Arm

COMPARE TO

CASE CX17C	John Deere 17P	Takeuchi TB216
CAT 301.7 CR	Kobelco SK17SR-6E	Volvo ECR18E
Develon DX17X-7	Kubota U17	Yanmar Vi017-1E
Hyundai R17Z-9A		

ZX26U-5N



ZX26U-5N SPECIFICATIONS

Weight Canopy: 5,560 lbs / 2,520 kg
 Cab: 5,890 lbs / 2,670 kg

Overall Width 4' 11" / 1.50 m

Net Rated Power 20.3 HP / 14.9 kW

Engine Yanmar 3TNV80F

Aux. Hyd. Flow 12.2 GPM / 46.3 LPM

Arm Length* 3' 10" / 1.17 m

Max Digging Reach
at Ground Level 15' 0" / 4.57 m

Max Dig Depth 8' 6" / 2.59 m

Arm Breakout 3,410 lbf / 15.17 kN

Bucket Breakout 4,994 lbf / 220.30 kN

*Rubber Shoe, 3' 10" Arm



COMPARE TO

Bobcat E26

CASE CX26C

CAT 302.7 CR

Develon DX27Z-7

John Deere 26P

Hyundai HX27AZ

Kubota U27-4

Takeuchi TB225

SANY SY26U

Volvo ECR25D

Yanmar Vi025-6B

ZX30U-5N



ZX30U-5N SPECIFICATIONS

Weight	Canopy: 6,680 lbs / 3,030 kg Cab: 7,055 lbs / 3,200 kg
Overall Width	5' 1" / 1.55 m
Net Rated Power	23.7 HP / 17.4 kW
Engine	Yanmar 3TNV88F
Aux. Hyd. Flow	16.2 GPM / 61.2 LPM
Arm Length*	3' 10" / 1.17 m
Max Digging Reach at Ground Level	15' 7" / 4.75 m
Max Dig Depth	9' 2" / 2.79 m
Arm Breakout	3,790 lbf / 17.0 kN
Bucket Breakout	6,110 lbf / 27.0 kN

*Rubber Shoe, 3' 10" Arm

COMPARE TO

Bobcat E32	Hyundai R30Z-9AK	Komatsu PC30MR-5
CASE CX30C	John Deere 30P	Takeuchi TB230
CAT 303 CR		

ZX35U-5N



ZX35U-5N SPECIFICATIONS

Weight Canopy: 8,157 lbs / 3,700 kg
 Cab: 8,532 lbs / 3,870 kg

Overall Width 5' 9" / 1.74 m

Net Rated Power 23.7 HP / 17.4 kW

Engine Yanmar 3TNV88F

Aux. Hyd. Flow 16.2 GPM / 61.2 LPM

Arm Length* 5' 8" / 1.72 m

Max Digging Reach
at Ground Level 17' 9" / 5.41 m

Max Dig Depth 11' 4" / 3.46 m

Arm Breakout 3,792 lbf / 16.9 kN

Bucket Breakout 6,085 lbf / 27.1 kN

*Rubber Shoe, 5' 8" Arm



COMPARE TO

Bobcat E35

CASE CX37C

CAT 303.5 CR

Develon DX35Z-7

Hyundai HX35AZ

John Deere 35P

Komatsu PC35MR-5

Kubota U35-4

SANY SY35U

Takeuchi TB235-2

Volvo EC37

Yanmar Vi035-6A

ZX50U-5N



ZX50U-5N SPECIFICATIONS

Weight Canopy: 11,054 lbs / 5,014 kg
 Cab: 11,341 lbs / 5,144 kg

Overall Width 6' 7" / 2.0 m

Net Rated Power 36.8 HP / 27.1 kW

Engine Yanmar 4TNV88C

Aux. Hyd. Flow 23.1 GPM / 87.5 LPM

Arm Length* 5' 7" / 1.69 m

Max Digging Reach
at Ground Level 20' 1" / 6.13 m

Max Dig Depth 12' 7" / 3.83 m

Arm Breakout 4,718 lbf / 21.0 kN

Bucket Breakout 8,267 lbf / 36.8 kN

*Rubber Shoe, 5' 7" Arm

COMPARE TO

Bobcat E55	Hyundai HX48AZ	SANY SY50U
CASE CX50D	John Deere 50P	Takeuchi TB250-2
CAT 305 CR	Komatsu PC45MR-5	Volvo ECR50
Develon DX50Z-7	Kubota U48-5	Yanmar Vi050-6A



ZX60USB-5N



ZX60USB-5N SPECIFICATIONS

Weight 14,021 lbs / 6,340 kg

Overall Width 6' 7" / 2.0 m

Net Rated Power 53.8 HP / 39.6 kW

Engine Yanmar 4TNV98C

Aux. Hyd. Flow 24.2 GPM / 90 LPM

Arm Length* 6' 1" / 1.85 m

Max Digging Reach at Ground Level 21' 1" / 6.42 m

Max Dig Depth 13' 6" / 4.12 m

Arm Breakout 6,063 lbf / 27.0 kN

Bucket Breakout 9,237 lbf / 41.1 kN

*Rubber Shoe, 6' 1" Arm



COMPARE TO

Bobcat E60

CASE CX60C

CAT 306 CR

Develon DX62R-7

Hyundai HX60A

John Deere 60P

Kubota KX057-5

SANY SY60C

Volvo EC60E

Yanmar ViO55-6A

ZX75US-7



ZX75US-7 SPECIFICATIONS

Weight	18,600 lbs / 8,418 kg
Overall Width	7' 5" / 2.26 m
Net Rated Power	63.7 HP / 47.5 kW
Engine	Yanmar 4TNV98CT
Aux. Hyd. Flow	Std: 18 GPM / 68 LPM Opt: Max 36 GPM / 136 LPM
Arm Length*	6' 11" / 2.12 m
Max Digging Reach at Ground Level	22' 1" / 6.72 m
Max Dig Depth	15' 3" / 4.65 m
Arm Breakout	7,755.9 lbf / 34.5 kN
Bucket Breakout	12,926.5 lbf / 57.5 kN

*Pad Crawler Shoe, 6' 11" Arm

COMPARE TO

CASE CX75C SR	Kobelco SK75SR-7	Link Belt 75 X3
CAT 307.5	Komatsu PC78US-11	SANY SY75C
John Deere 75P		

ZX85USB-7



ZX85USB-7 SPECIFICATIONS

Weight 19,500 lbs / 8,858 kg

Overall Width 7' 5" / 2.26 m

Net Rated Power 63.7 HP / 47.5 kW

Engine Yanmar 4TNV98CT-WHBW

Aux. Hyd. Flow Std: 18 GPM / 68 LPM
Opt: Max 36 GPM / 136 LPM

Arm Length* 6' 11" / 2.12 m

Max Digging Reach at Ground Level 24' 4" / 7.42 m

Max Dig Depth 14' 10" / 4.53 m

Arm Breakout 7,755.9 lbf / 34.5 kN

Bucket Breakout 12,926.5 lbf / 57.5 kN

*Pad Crawler Shoe, 6' 11" Arm



COMPARE TO

Bobcat E88

CASE CX80C

CAT 308 CR

Hyundai HX85A

John Deere 85P

Kobelco SK85CS-7

Komatsu PC88MP-11

Kubota KX080-5

Link Belt 80X3

SANY SY80U

Takeuchi TB290

Volvo ECR88D

Yanmar Vi080-7

ZX130-7H



ZX130-7H* SPECIFICATIONS

Weight 30,865 lbs / 14,000 kg

Overall Width 8' 6" / 2.59 m

Net Rated Power 100 HP / 74.9 kW

Engine Isuzu AR-4JJ1X

Aux. Hyd. Flow 27.7 GPM / 105 LPM

Arm Length 9' 11" / 3.01 m

Max Digging Reach at Ground Level 28' 5" / 8.65 m

Max Dig Depth 19' 9" / 6.03 m

Arm Breakout 13,713 lbf / 61 kN

Bucket Breakout 23,380 lbf / 104 kN

*24" Track Shoes & No Blade

COMPARE TO

CAT 313	Kobelco SK130LC-11	Takeuchi TB2150
Develon DX140LC-7K	Komatsu PC130LC-11	SANY SY135C
Hyundai HX140A L	Link Belt 130 X4	Volvo EC140E
John Deere 130P		

ZX135US-7H



ZX135US-7H* SPECIFICATIONS

Weight 31,967 lbs / 14,500 kg

Overall Width 8' 6" / 2.59 m

Net Rated Power 100 HP / 74.9 kW

Engine Isuzu AR-4JJ1X

Aux. Hyd. Flow 27.7 GPM / 105 LPM

Arm Length 9' 11" / 3.01 m

Max Digging Reach at Ground Level 28' 7" / 8.72 m

Max Dig Depth 19' 7" / 5.98 m

Arm Breakout 13,713 lbf / 61 kN

Bucket Breakout 23,380 lbf / 104 kN

*24" Track Shoes & No Blade

COMPARE TO

Bobcat E145

CASE CX145D SR

CAT 315

Develon DX140LCR-7

Hyundai HX145A LCR

John Deere 135P

Kobelco SK140SRLC-7

Komatsu PC138US-11

Link Belt 145 X4

SANY SY155U

Volvo ECR145



ZX160LC-7H



ZX160LC-7H* SPECIFICATIONS

Weight	39,683 lbs / 18,000 kg
Overall Width	8' 6" / 2.6 m
Net Rated Power	132 HP / 98.6 kW
Engine	Yanmar 4TN107
Aux. Hyd. Flow	50 GPM / 190 LPM
Arm Length	10' 1" / 3.08 m
Max Digging Reach at Ground Level	30' 1" / 9.16 m
Max Dig Depth	21' 4" / 6.49 m
Arm Breakout	18,209 lbf / 81 kN
Bucket Breakout	25,179 lbf / 112 kN

*24" Track Shoes

COMPARE TO

Bobcat E165	Hyundai HX160A L	Komatsu PC170-11
CASE CX170E	John Deere 160P	Link Belt 160 X4
CAT 317	Kobelco SK170LC-11	Volvo EX160E
Develon DX170LC-5		

ZX190LC-7H



ZX190LC-7H SPECIFICATIONS

Weight 43,872 lbs / 19,900 kg

Overall Width 9' 10" / 3 m

Net Rated Power 132 HP / 98.6 kW

Engine Yanmar 4TN107

Aux. Hyd. Flow 50 GPM / 190 LPM

Arm Length 10' 6" / 3.21 m

Max Digging Reach at Ground Level 32' 1" / 9.79 m

Max Dig Depth 23' 2" / 7.07 m

Arm Breakout 18,884 lbf / 84 kN

Bucket Breakout 28,551 lbf / 127 kN



COMPARE TO

CASE CX190E

Hyundai HX180A L

Link Belt 190 X4S

Develon DX180LC-5

John Deere 200G

Volvo EC200E

ZX210LC-7H



ZX210LC-7H SPECIFICATIONS

Weight	50,927 lbs / 23,100 kg
Overall Width	10' 6" / 3.19 m
Net Rated Power	164 HP / 122 kW
Engine	Isuzu 4HK1
Aux. Hyd. Flow	56 GPM / 212 LPM
Arm Length	9' 7" / 2.91 m
Max Digging Reach at Ground Level	32' 0" / 9.75 m
Max Dig Depth	21' 11" / 6.67 m
Arm Breakout	25,628 lbf / 114 kN
Bucket Breakout	35,520 lbf / 158 kN

COMPARE TO

CASE CX220E	John Deere 210P	Link Belt 220X4S
CAT 320	Kobelco SK210LC-11	SANY SY215C LC
Develon DX200LC-7	Komatsu PC210LC-11	Volvo EC210
Hyundai HX210A L	Link Belt 210X4	

ZX245USLC-7H



ZX245USLC-7H SPECIFICATIONS

Weight 58,202 lbs / 26,400 kg

Overall Width 10' 6" / 3.19 m

Net Rated Power 164 HP / 122 kW

Engine Isuzu 4HK1

Aux. Hyd. Flow 56 GPM / 212 LPM

Arm Length 9' 7" / 2.91 m

Max Digging Reach at Ground Level 32' 6" / 9.9 m

Max Dig Depth 21' 8" / 6.61 m

Arm Breakout 25,628 lbf / 114 kN

Bucket Breakout 35,520 lbf / 158 kN



COMPARE TO

CASE CX245D SR

Hyundai HX235A LCR

Komatsu PC238USLC-11

CAT 325

John Deere 245P

Link Belt 245 X4

Develon DX235LCR-7

Kobelco SK230SRLC-7

Volvo ECR235E

ZX250LC-7H



ZX250LC-7H SPECIFICATIONS

Weight	60,186 lbs / 27,300 kg
Overall Width	11' 1" / 3.39 m
Net Rated Power	177 HP / 132 kW
Engine	Isuzu 4HK1
Aux. Hyd. Flow	59 GPM / 244 LPM
Arm Length	11' 10" / 3.61 m
Max Digging Reach at Ground Level	35' 3" / 10.75 m
Max Dig Depth	25' 0" / 7.61 m
Arm Breakout	25,403 lbf / 113 kN
Bucket Breakout	42,264 lbf / 188 kN

COMPARE TO

CASE CX260E	John Deere 250P	Link Belt 250 X4
CAT 326	Kobelco SK260LC-11	SANY SY265C LC
Develon DX255LC-7	Komatsu PC240-11	Volvo EC250E
Hyundai HX260A L		

ZX300LC-7H



ZX300LC-7H SPECIFICATIONS

Weight	69,005 lbs / 31,300 kg
Overall Width	11' 1" / 3.39 m
Net Rated Power	249 HP / 186 kW
Engine	Isuzu 6HK1X
Aux. Hyd. Flow	62 GPM / 236 LPM
Arm Length	12' 4" / 3.76 m
Max Digging Reach at Ground Level	36' 5" / 11.10 m
Max Dig Depth	25' 10" / 7.87 m
Arm Breakout	32,372 lbf / 144 kN
Bucket Breakout	45,411 lbf / 202 kN



COMPARE TO

CASE CX300E	John Deere 300P	Link Belt 300 X4
CAT 330	Kobelco SK300LC-11	SANY SY335C
Develon DX300LC-7	Komatsu PC290-11	Volvo EC300
Hyundai HX300A L		

ZX345USLC-7H



ZX345USLC-7H SPECIFICATIONS

Weight **79,366 lbs / 36,000 kg**

Overall Width **11' 1" / 3.39 m**

Net Rated Power **249 HP / 186 kW**

Engine **Isuzu 6HK1X**

Aux. Hyd. Flow **62 GPM / 236 LPM**

Arm Length **12' 4" / 3.76 m**

Max Digging Reach at Ground Level **36' 10" / 11.22 m**

Max Dig Depth **24' 10" / 7.57 m**

Arm Breakout **32,372 lbf / 126 kN**

Bucket Breakout **45,411 lbf / 202 kN**

COMPARE TO

CASE CX365E SR

CAT 335

Develon DX350LCR-7

Hyundai HX355A LCR

John Deere 345P

Kobelco SK380SRLC-7

Volvo ECR355E

ZX350LC-7H



ZX350LC-7H SPECIFICATIONS

Weight 80,248 lbs / 36,400 kg

Overall Width 11' 1" / 3.39 m

Net Rated Power 271 HP / 202 kW

Engine Isuzu 6HK1X

Aux. Hyd. Flow 76 GPM / 288 LPM

Arm Length 13' 2" / 4.00 m

Max Digging Reach at Ground Level 38' 3" / 11.67 m

Max Dig Depth 26' 10" / 8.18 m

Arm Breakout 35,745 lbf / 159 kN

Bucket Breakout 55,303 lbf / 246 kN



COMPARE TO

CASE CX350D

John Deere 350P

Link Belt 350 X4

CAT 336

Kobelco SK350LC-11

SANY SY385C LC

Develon DX350LC-7

Komatsu PC360LC-11

Volvo EC350E

Hyundai 350A L

ZX490LC-7H



ZX490LC-7H SPECIFICATIONS

Weight 108,247 lbs / 49,100 kg*

Overall Width 12' 6" / 3.81 m

Net Rated Power 388 HP / 289 kW

Engine Isuzu 6WG1

Aux. Hyd. Flow 102 GPM / 385 LPM

Arm Length 12' 10" / 3.9 m

Max Digging Reach at Ground Level 40' 3" / 12.28 m

Max Dig Depth 27' 2" / 8.27 m

Arm Breakout 45,187 lbf / 201 kN

Bucket Breakout 64,295 lbf / 286 kN

*Fixed Undercarriage

COMPARE TO

CASE CX490D	Hyundai HX480A L	Link Belt 490 X4
CAT 350 / 352	Komatsu PC490LC-11	Volvo EC480E
Develon DX490LC-7	John Deere 470P	

ZX690LC-7H



ZX690LC-7H SPECIFICATIONS

Weight 152,780 lbs / 69,300 kg

Overall Width 14' 4" / 4.36 m

Net Rated Power 465 HP / 347 kW

Engine Isuzu 6WG1

Aux. Hyd. Flow 129 GPM / 489 LPM

Arm Length 13' 9" / 4.2 m

Max Digging Reach at Ground Level 44' 9" / 13.63 m

Max Dig Depth 30' 1" / 9.18 m

Arm Breakout 51,931 lbf / 231 kN

Bucket Breakout 72,838 lbf / 324 kN



COMPARE TO

CASE 750D
CAT 374

John Deere 670P
Komatsu PC650LC-11

Link Belt 750 X4
Volvo EC750E

ZX890LC-7H



ZX890LC-7H SPECIFICATIONS

Weight 189,157 lbs / 85,800 kg

Overall Width 14' 7" / 4.45 m

Net Rated Power 510 HP / 380 kW

Engine Isuzu 6WG1

Aux. Hyd. Flow 147 GPM / 556 LPM

Arm Length 14' 5" / 4.40 m

Max Digging Reach at Ground Level 48' 0" / 14.64 m

Max Dig Depth 31' 5" / 9.57 m

Arm Breakout 62,947 lbf / 280 kN

Bucket Breakout 89,699 lbf / 399 kN

COMPARE TO

CAT 395	Hyundai HX800A L	Komatsu PC900LC-11
Develon DX800LC-7	John Deere 870P	Volvo EC950F

FULL LINEUP

COMPACT EXCAVATORS



ZX17U-5N

NRP 14.7 HP (10.8 kW)
OW 3,790 lbs (1,720 kg)



ZX26U-5N

NRP 20.3 HP (14.9 kW)
OW Canopy: 5,560 lbs (2,520 kg)
OW Cab: 5,890 lbs (2,670 kg)



ZX50U-5N

NRP 36.8 HP (27.1 kW)
OW Canopy: 11,054 lbs (5,014 kg)
OW Cab: 11,341 lbs (5,144 kg)



ZX60USB-5N

NRP 53.8 HP (39.6 kW)
OW 13,426 lbs (6,090 kg)

MEDIUM EXCAVATORS



ZX130-7H

NRP 100 HP (74.9 kW)
OW 30,865 lbs (14,000 kg)



ZX135US-7H

NRP 100 HP (74.9 kW)
OW 31,967 lbs (14,500 kg)



ZX210LC-7H

NRP 164 HP (122 kW)
OW 50,927 lbs (23,100 kg)



ZX245USLC-7H

NRP 164 HP (122 kW)
OW 58,202 lbs (26,400 kg)



ZX345USLC-7H

NRP 249 HP (186 kW)
OW 79,366 lbs (36,000 kg)



ZX350LC-7H

NRP 271 HP (202 kW)
OW 80,248 lbs (36,400 kg)

LARGE EXCAVATORS



ZX490LC-7H

NRP 388 HP (289 kW)
OW 108,247 lbs (49,100 kg)



ZX690LC-7H

NRP 465 HP (347 kW)
OW 152,780 lbs (69,300 kg)

NRP Net Rated Power
OW Operating Weight



ZX30U-5N

NRP 23.7 HP (17.4 kW)
OW Canopy: 6,680 lbs (3,030 kg)
OW Cab: 7,055 lbs (3,200 kg)



ZX35U-5N

NRP 23.7 HP (17.4 kW)
OW Canopy: 8,157 lbs (3,700 kg)
OW Cab: 8,532 lbs (3,870 kg)



ZX75US-7

NRP 63.7 HP (47.5 kW)
OW 18,600 lbs (8,418 kg)



ZX85USB-7

NRP 63.7 HP (47.5 kW)
OW 19,500 lbs (8,858 kg)



ZX160LC-7H

NRP 132 HP (98.6 kW)
OW 39,683 lbs (18,000 kg)



ZX190LC-7H

NRP 132 HP (98.6 kW)
OW 43,872 lbs (19,900 kg)



ZX250LC-7H

NRP 177 HP (132 kW)
OW 60,186 lbs (27,300 kg)



ZX300LC-7H

NRP 249 HP (186 kW)
OW 69,005 lbs (31,300 kg)



ZX890LC-7H

NRP 510 HP (380 kW)
OW 189,157 lbs (85,800 kg)

HITACHI

Reliable Solutions

LANDCROS



Hitachi Construction Machinery Americas
© 2026 All Rights Reserved
Global Pub #: HS-EN012-NA-US-R
Stay Connected @HitachiConstructionAmericas

www.hitachicm.us

